

GENERAL PRODUCT DESCRIPTION

Capa[®] 2100 is a standard grade linear polyester diol derived from caprolactone monomer, terminated by primary hydroxyl groups. It has a molecular weight of 1000 and a typical OH value of 112 mg KOH/g.

The product has been specially developed as an intermediate for the production of high grade polyurethane elastomers. In addition, Capa[®] 2100 can be used in polyurethane adhesive, surface coating and flexible foam applications, and as a resin intermediate.

TYPICAL PROPERTIES

Physical Form	White paste
Mean Molecular Weight	1000
Melting Point	30°C - 40°C
Hydroxyl Value	112 mg KOH/g
Acid Value	<0.25 mg KOH/g
Water Content	<0.02%
Viscosity at 60°C	150 mPa.s

DENSITIES

The typical specific gravity (SG) of the material, measured at 55°C c.f. water at 20°C, is 1.072.

SOLUBILITY PARAMETERS

The solubility parameter (δ) is 9.34 – 9.43 (cal/cm³)^{1/2}.

HANDLING AND STORAGE

Capa[®] 2100 is supplied in lacquered mild steel drums containing 200 kg net. The product should continue to be stored in air-tight containers to prevent moisture pick-up from the atmosphere.

For further information please contact:

Perstorp UK Limited
Baronet Road
Warrington, Cheshire WA4 6HA
United Kingdom
Tel. +44 (0)1925 643210
Fax. +44 (0)1925 232207
contact.capa@perstorp.com
www.caprolactones.com

Perstorp Specialty Chemicals AB
SE-284 80 Perstorp,
Sweden
Tel. +46 435 38000
Fax +46 435 37067
technical.support@perstorp.com
www.perstorp.com