
GENERAL PRODUCT DESCRIPTION

Capa[®] FB540 is a film grade thermoplastic polycaprolactone. It has been specifically designed to be processed on conventional film blowing equipment.

It is supplied as a resin filled with 40% mineral filler and can be used in a variety of film applications.

TYPICAL PROPERTIES

Physical Form	Approx. 3 mm pellets
Mean Molecular Weight	>100,000
Melting Point	58 °C - 60 °C
Water Content	<1.0%
Colour of 30% m/m solution (Hazen)	<75
Melt index	<4 with 2.16 kg standard die at 190°C
Filler	Calcium Carbonate

HANDLING AND STORAGE

Capa[®] FB540 is supplied in quantities of 20 kg net packed in paper sacks on pallets of 1000 kg. Bulk quantities can be supplied in 500 kg bags. Capa[®] FB540 should be stored in a dry place away from sources of heat.

For further information please contact:

Perstorp UK Limited
Baronet Road
Warrington, Cheshire WA4 6HA
United Kingdom
Tel. +44 (0)1925 643210
Fax. +44 (0)1925 232207
contact.capa@perstorp.com
www.caprolactones.com

Perstorp Specialty Chemicals AB
SE-284 80 Perstorp,
Sweden
Tel. +46 435 38000
Fax +46 435 37067
technical.support@perstorp.com
www.perstorp.com