



**SOLVAY**  
CAPROLACTONES

# CAPA<sup>®</sup> HC1060

## GENERAL PRODUCT DESCRIPTION

CAPA<sup>®</sup> HC1060 is a polycaprolactone polyester diol with a pendant carboxylic functional group. It is particularly suitable for the production of aqueous polyurethane dispersions for use in water-borne adhesives and surface coatings.

## TYPICAL PROPERTIES

Physical Form	Soft white waxy solid
Mean Molecular Weight	600
Melting Point	35°C-40°C
Hydroxyl Value	180 mg KOH/g
Acid Value	<90 mg KOH/g
Water Content	<0.5%
Viscosity at 60°C	545 mPa.s

## HANDLING AND STORAGE

CAPA<sup>®</sup> HC1060 is supplied in lacquered mild steel drums containing 200kg nett. The product should continue to be stored in air-tight containers to prevent moisture pick-up from the atmosphere.

### For further information please contact:

Solvay Caprolactones  
Baronet Road  
Warrington  
Cheshire WA4 6HB  
United Kingdom

Telephone: +44 (0) 1925 651277  
Fax: +44 (0) 1925 232207  
E-mail: [contact.capa@solvay.com](mailto:contact.capa@solvay.com)  
Website: [www.solvaycaprolactones.com](http://www.solvaycaprolactones.com)

**CAPA<sup>®</sup>**  
For  
**SPEARHEAD  
PERFORMANCE**