
GENERAL PRODUCT DESCRIPTION

Capa[®] 2077A is a premium grade polycaprolactone polyester diol. It has a molecular weight of 750 and a typical OH value of 150 mg KOH/g.

The product has been specifically designed for use in speciality coatings and polyurethane elastomers.

TYPICAL PROPERTIES

Physical Form	Soft white paste
Mean Molecular Weight	750
Melting Point	20 °C - 30 °C
Hydroxyl Value	150 mg KOH/g
Acid Value	<0.05 mg KOH/g
Water Content	<0.02%
Viscosity at 60 °C	85 mPa.s

SOLUBILITY PARAMETERS

The solubility parameter (δ) is 9.34 – 9.43 (cal/cm³)^{1/2}.

HANDLING AND STORAGE

Capa[®] 2077A is supplied in lacquered mild steel drums containing 200 kg net. The product should continue to be stored in air-tight containers to prevent moisture pick-up from the atmosphere.

For further information please contact:

Perstorp UK Limited
Baronet Road
Warrington, Cheshire WA4 6HA
United Kingdom
Tel. +44 (0)1925 643500
Fax. +44 (0)1925 232207
contact.capa@perstorp.com
www.perstorpcaprolactones.com

Perstorp Specialty Chemicals AB
SE-284 80 Perstorp,
Sweden
Tel. +46 435 38000
Fax +46 435 37067
technical.support@perstorp.com
www.perstorp.com