

GENERAL PRODUCT DESCRIPTION

Capa[®] 2203A is a premium grade linear polycaprolactone diol. It has a molecular weight 2000 and a typical OH value of 56 mg KOH/g.

The product has been specially developed to produce high performance cast or thermoplastic elastomers. It offers improved properties over elastomers made from standard Capa[®] materials of better prepolymer stability and improved hydrolysis resistance.

TYPICAL PROPERTIES

Physical Form	White waxy solid
Mean Molecular Weight	2000
Melting Point	40°C - 50°C
Hydroxyl Value	56 mg KOH/g
Acid Value	<0.05 mg KOH/g
Water Content	<0.02%
Viscosity at 60°C	460 mPa.s

DENSITIES

The typical specific gravity (SG) of the material, measured at 55°C c.f. water at 20°C, is 1.071.

SOLUBILITY PARAMETERS

The solubility parameter (δ) is 9.34 – 9.43 (cal/cm³)^{1/2}.

HANDLING AND STORAGE

Capa[®] 2203A is supplied in 200 kg net lacquered mild steel drums. It should continue to be stored in air-tight containers to prevent moisture pick-up from the atmosphere.

For further information please contact:

Perstorp UK Limited
Baronet Road
Warrington, Cheshire WA4 6HA
United Kingdom
Tel. +44 (0)1925 643500
Fax. +44 (0)1925 232207
contact.capa@perstorp.com
www.perstorpcaprolactones.com

Perstorp Specialty Chemicals AB
SE-284 80 Perstorp,
Sweden
Tel. +46 435 38000
Fax +46 435 37067
technical.support@perstorp.com
www.perstorp.com