

## GENERAL PRODUCT DESCRIPTION

Capa<sup>®</sup> FB100 is a film grade thermoplastic polycaprolactone. It has been specifically designed to be processed on conventional film blowing equipment. It is supplied as a 100% resin and can be used in a variety of blown film and adhesive applications.

## TYPICAL PROPERTIES

<b>Physical Form</b>	<b>Approx. 3 mm pellets</b>
<b>Mean Molecular Weight</b>	<b>&gt;100,000</b>
<b>Melting Point</b>	<b>58 °C - 60 °C</b>
<b>Water Content</b>	<b>&lt;1.0%</b>
<b>Colour of 30% m/m solution (Hazen)</b>	<b>&lt;75</b>
<b>Melt index</b>	<b>&lt;4 with 2.16 kg standard die at 190°C</b>

## HANDLING AND STORAGE

Capa<sup>®</sup> FB100 is supplied in quantities of 20 kg net packed in paper sacks on pallets of 1000 kg. Bulk quantities can be supplied in 500 kg bags. Capa<sup>®</sup> FB100 should be stored in a dry place away from sources of heat.

For further information please contact:

Perstorp UK Limited  
Baronet Road  
Warrington, Cheshire WA4 6HA  
United Kingdom  
Tel. +44 (0)1925 643500  
Fax. +44 (0)1925 232207  
[contact.capa@perstorp.com](mailto:contact.capa@perstorp.com)  
[www.perstorpcaprolactones.com](http://www.perstorpcaprolactones.com)

Perstorp Specialty Chemicals AB  
SE-284 80 Perstorp,  
Sweden  
Tel. +46 435 38000  
Fax +46 435 37067  
[technical.support@perstorp.com](mailto:technical.support@perstorp.com)  
[www.perstorp.com](http://www.perstorp.com)