
GENERAL PRODUCT DESCRIPTION

Capa[®] HC1200 is a polycaprolactone polyester diol with a pendant carboxylic functional group. It has a molecular weight of 2000 and a typical OH value of 56mg KOH/g. It has been specifically designed for use in speciality water borne polyurethane dispersions, such as adhesives and coatings.

TYPICAL PROPERTIES

Physical Form	Hard white waxy solid
Mean Molecular Weight	2000
Melting Point	45 °C - 50 °C
Hydroxyl Value	56 mg KOH/g
Acid Value	<30 mg KOH/g
Water Content	<0.1%
Viscosity at 60 °C	940 mPa.s

HANDLING AND STORAGE

Capa[®] HC1200 is supplied in lacquered mild steel drums containing 200kg net. The product should continue to be stored in air-tight containers to prevent moisture pick-up from the atmosphere.

For further information please contact:

Perstorp UK Limited
Baronet Road
Warrington, Cheshire WA4 6HA
United Kingdom
Tel. +44 (0)1925 643500
Fax. +44 (0)1925 232207
contact.capa@perstorp.com
www.perstorpcaprolactones.com

Perstorp Specialty Chemicals AB
SE-284 80 Perstorp,
Sweden
Tel. +46 435 38000
Fax +46 435 37067
technical.support@perstorp.com
www.perstorp.com